

DESIGN DS	DRAWN BY	DART AEROSPACE LTD VICTORIA INTERNATIONAL AIRPORT, CANADA	
CHECKED	APPROVED	DEO 9097 SHEE	REV. A
97. 12. 14		TITLE 204/205 SKIDTUBE DRILLING CHANGE	SCALE

DART ENGINEERING ORDER

TO AMEND DWGS: D2580 REV. B

D2590 REV. B

D2596 REV. B


D2597 REV. C

SUPERCEDED BY

98.01.17 DS

SEE DISGO | DISGO REV.C

HOLE PATTERN FOR 204/205 SKIDTUBES SHOULD BE ADJUSTED AS FOLLOWS:



- NOTE: 1. = EXISTING HOLE

 O = NEW HOLE
 - 2. WEB HOLES SHOULD BE DRILLED TO \$0.63 AS PER DWGS
 DZ596 /DZ597 (OPEN TO 0.500 IF ASSEMBLED TUBE IS BEING MODIFIED)
 - 3. SKIDTUBE HOLES SHOULD BE DRILLED TO \$0,500 AND DZS79 SPACERS SHOULD BE INSTALLED PER DWGS DZS80 / DZS90.
 - 4. DZS94 PLUGS SHOULD NOW BE INSTALLED IN HOLE MARKED

 191 ABOVE (TOTAL NUMBER OF PLUGS INCREASED FROM

 14 TO 16)